

## HOT JET S




As the most compact hand tool from Leister, the HOT JET S' low weight of just 1.3 lbs, incl. cord and slim handle, ensures fatigue-free welding and high power.



- The smallest hand tool
- Electronic steplessly controlled temperature
- Electronic steplessly controlled air flow
- Electronic heating element protection
- Low noise
- Integrated flexible tool stand

### SPECIFICATIONS

#### HOT JET S 100 V

Voltage	V~	100
Power consumption	W	460
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Air flow (20°C)	l/min	20 – 80
Pressure static	Pa	max. 1600 (16 mbar)
Noise emission level LpA	dB	59
Size (L x ø)	mm	235 x 70, handle Ø 40
Weight	kg	0.6 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		

#### HOT JET S 120 V

Voltage	V~	120
---------	----	-----

## Plastic Welding &gt; Hand tools &gt; HOT JET S

Power consumption	W	460
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Air flow (20°C)	l/min	20 – 80
Pressure static	Pa	max. 1600 (16 mbar)
Noise emission level LpA	dB	59
Size (L x ø)	mm	235 x 70, handle Ø 40
Weight	kg	0.6 (with 3 m cord)

Marking of conformity



Approval mark



Certification scheme

CCA

Protection class II



## HOT JET S 230 V

Voltage	V~	230
Power consumption	W	460
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Air flow (20°C)	l/min	20 – 80
Pressure static	Pa	max. 1600 (16 mbar)
Noise emission level LpA	dB	59
Size (L x ø)	mm	235 x 70, handle Ø 40
Weight	kg	0.6 (with 3 m cord)

Marking of conformity



Approval mark



Certification scheme

CCA

Protection class II





## ACCESSORIES



Tubular nozzle  $\varnothing$  5 mm push-fit on HOT JET S, LE MINI, LE MINI SENSOR  
107.144 - Tubular nozzle  $\varnothing$  5 mm, push-fit



Wide slot nozzle 20 mm push-fit on HOT JET S  
107.142 - Wide slot nozzle 20 mm, push-fit



Sieve reflector 35 x 20 mm push-fit on HOT JET S  
107.310 - Sieve reflector 35 x 20 mm, push-fit



Spoon reflector 25 x 30 mm push-fit on HOT JET S  
107.312 - Spoon reflector 25 x 30 mm, push-fit



Sieve reflector 50 x 35 mm push-fit on HOT JET S  
107.311 - Sieve reflector 50 x 35 mm, push-fit



Pressure roller 28 mm (PTFE), with ball bearings  
106.976 - Pressure roller 28 mm (PTFE)with ball bearings



Pressure roller 28 mm (silicon), with ball bearings  
106.977 - Pressure roller 28 mm (silicon), with ball bearings

## Plastic Welding &gt; Hand tools &gt; HOT JET S



One-arm pressure roller 40 mm, with ball bearings (silicon)

106.975 - One-arm pressure roller 40 mm, with ball bearings (silicon)




Customs seal roller, with ball bearings

106.981 - Customs seal roller, with ball bearings



Pressure roller with ball bearings (brass), with ball bearings

106.972 - Pressure roller with ball bearings (brass), with ball bearings



Tacking nozzle push-fit on tubular nozzle ø 5 mm

106.996 - Tacking nozzle, push-fit on tubular nozzle Ø 5mm



Speed welding nozzle 4.5 x 12mm for fillet seams

107.139 - Speed welding nozzle 4.5 x 12mm for fillet seams, push-fit on tubular nozzle ø 5mm



Speed welding nozzle for tape 8 mm push-fit on tubular nozzle Ø 5mm

107.137 - Speed welding nozzle for tape 8 mm, push-fit on tubular nozzle Ø 5mm




Speed welding nozzle with small air-slide, push-fit on Tubular nozzle ø 5mm

105.431 - Speed welding nozzle 3 mm, small air-slide, push-fit on tubular nozzle Ø 5 mm

105.432 - Speed welding nozzle 4 mm, small air-slide, push-fit on tubular nozzle Ø 5mm

105.433 - Speed welding nozzle 5 mm, small air-slide, push-fit on Tubular nozzle Ø 5 mm




Speed welding nozzle 3, 4, 5 mm push-fit on tubular nozzle Ø 5 mm

106.989 - Speed welding nozzle 3 mm, push-fit on tubular nozzle Ø 5 mm

106.990 - Speed welding nozzle 4 mm push-fit, on tubular nozzle Ø 5 mm

106.991 - Speed welding nozzle 5 mm, push-fit on tubular nozzle Ø 5 mm


## Plastic Welding &gt; Hand tools &gt; HOT JET S



Speed welding nozzle 5.7, 7 mm push-fit on tubular nozzle Ø 5 mm

106.992 - Speed welding nozzle 5.7 mm, push-fit on tubular nozzle Ø 5 mm

106.993 - Speed welding nozzle 7 mm, push-fit on tubular nozzle Ø 5 mm



Sieve reflector 12 x 10 mm push-fit on tubular nozzle Ø 5mm

107.324 - Sieve reflector 12 x 10 mm, push-fit on tubular nozzle Ø 5mm